



ROOF / WALL FLASHING DETAIL

- FINISH COAT
- BROWN COAT
- SCRATCH COAT
- LATH
- WRB-BOND BREAK
- WRB-DRAINAGE PLANE
- SHEATHING
- LAP WRBs AND TAPE OVER THE WEEP SCREED ATTACHMENT FLANGE
- SAF
- WEEP SCREED

DO NOT PAINT OR SEAL THE INTERFACE. THIS IS THE INTENDED WEEP POINT.

MIN. 5"x5" "L" TYPE GALVANIZED FLASHING

CAP SHINGLE - DO NOT NAIL. INSTALL WITH ROOF CEMENT.

1/4" LATH GAP MIN.

5" (MIN.)

2" (MIN.)

LEGEND

- SHEATHING, 'OSB', PLYWOOD, DENSGLASS
- SELF ADHERED FLASHING
- PLASTER ACCESSORY
- DRAINAGE PLANE WATER RESISTANT BARRIER (WRB)
- BOND BREAK WATER RESISTANT BARRIER (WRB)
- SELF FURRING (SF) LATH
- SCRATCH COAT
- STUCCO
- SILL SEAL
- FOAM ORNAMENTALS
- GALVANIZED METAL FLASHING



Florida Lath & Plaster Bureau (FLAPB) details are for illustration of construction methods. They are to be used as guidelines by the design and/or construction team. You should consult with your design and/or construction specialists for specific construction requirements. Some modification may be required for specific project conditions or to meet local building code. FLAPB makes no representation as to the suitability of any detail for specific use at any location on any project. A qualified, licensed architect or engineer must be consulted to specify the detail for any specific use at any location on a project.