












NOTE

1. IN EITHER CASE STUCCO CANNOT BE APPLIED TO CODE/ STANDARD COMPLIANT THICKNESS WITHOUT SOME TOLERANCE.
2. IN ORDER TO MAINTAIN THE REQUIRED 7/8" THICKNESS AND KEEP THE FINISH COAT PLANE TRUE AND PLUMB, THE STUCCO WOULD HAVE TO EXCEED THE THICKNESS ALLOWED BY C926, EITHER IN THE MIDDLE OR ON THE ENDS RESPECTIVELY.
3. RESULTING PLASTER THICKNESSES IN EXCESS OF THE ALLOWANCES OF TABLE 4 OF ASTM C926 TO BE EVALUATED BY A DESIGN PROFESSIONAL FOR CORRECTIVE OPTIONS.

LEGEND

	SHEATHING, 'OSB', PLYWOOD, DENSGLOSS
	SELF ADHERED FLASHING
	PLASTER ACCESSORY
	DRAINAGE PLANE WATER RESISTANT BARRIER (WRB)
	BOND BREAK WATER RESISTANT BARRIER (WRB)
	SELF FURRING (SF) LATH
	SCRATCH COAT
	STUCCO
	SILL SEAL
	FOAM ORNAMENTALS
	GALVANIZED METAL FLASHING

STUCCO THICKNESS VARIATIONS DUE TO FRAMING



Florida Lath & Plaster Bureau (FLAPB) details are for illustration of construction methods. They are to be used as guidelines by the design and/or construction team. You should consult with your design and/or construction specialists for specific construction requirements. Some modification may be required for specific project conditions or to meet local building code. FLAPB makes no representation as to the suitability of any detail for specific use at any location on any project. A qualified, licensed architect or engineer must be consulted to specify the detail for any specific use at any location on a project.